


Travi “HEB”



designazione	peso Kg/m.	sezione cmq.	dimensioni					caratteristiche riferite all'asse neutro					
			h mm.	b mm	a mm	e mm	r mm	X - X			Y - Y		
								J_x	$\frac{J_x}{V_x}$	i_x	J_y	$\frac{J_y}{V_y}$	i_y
								cm ⁴	cm ³	cm	cm ⁴	cm ³	cm
100	20,4	26,0	100	100	6	10	12	450	89,9	4,16	167	33,5	2,53
120	26,7	34,0	120	120	6,5	11	12	864	144	5,04	318	52,9	3,06
140	33,7	43,0	140	140	7	12	12	1510	216	5,93	550	78,5	3,58
160	42,6	54,3	160	160	8	13	15	2490	311	6,78	889	111	4,05
180	51,2	65,3	180	180	8,5	14	15	3830	426	7,66	1360	151	4,57
200	61,3	78,1	200	200	9	15	18	5700	570	8,54	2000	200	5,07
220	71,5	91,0	220	220	9,5	16	18	8090	736	9,43	2840	258	5,59
240	83,2	106	240	240	10	17	21	11260	938	10,3	3920	327	6,08
260	93,0	118	260	260	10	17,5	24	14920	1150	11,2	5130	395	6,58
280	103	131	280	280	10,5	18	24	1970	1380	12,1	6590	471	7,09
300	117	149	300	300	11	19	27	25170	1680	13,0	8560	571	7,58
320	127	161	320	300	11,5	20,5	27	30800	1930	13,8	9240	616	7,57
340	134	171	340	300	12	21,5	27	36660	2160	14,6	9690	646	7,53
360	142	181	360	300	12,5	22,5	27	43190	2400	15,5	10140	676	7,49
400	155	198	400	300	13,5	24	27	57680	2880	17,1	10820	721	7,40
450	171	218	450	300	14	26	27	79890	3550	19,1	11720	781	7,33
500	187	239	500	300	14,5	28	27	107200	4290	21,2	12620	842	7,27
550	199	254	550	300	15	29	27	136700	4970	23,2	13080	872	7,17
600	212	270	600	300	15,5	30	27	171000	5700	25,2	13500	902	7,08