

Travi "HEM" sollecitate a flessione

profilo	dimensioni				Peso Kg/mt	CARICO MASSIMO IN Kg UNIFORMEMENTE RIPARTITO (acciaio con carico di sicurezza OK=16Kg/mm ²)											
	Altezza mm.	Lar- ghezza mm.	Spessore			DISTANZA TRA GLI APPOGGI IN METRI											
			gambo mm.	ala mm.		2	3	4	5	6	7	8	9	10	11	12	
	100	120	106	12		20	41,8	12076	7981	5912	4654	3802	3181	2705	-	-	-
120	140	126	12,5	21	52,1	18327	12131	9007	7112	5771	4901	4191	3627	-	-	-	
140	160	146	13	22	63,2	26177	17346	12900	10205	8388	7072	6070	5276	4628	-	-	
160	180	166	14	23	76,2	36070	23920	17806	14108	11617	9816	8446	7363	6482	5747	-	
180	200	186	14,5	24	88,9	47693	31647	23580	18704	15423	13055	11256	9837	8685	7726	6911	
200	220	206	15	25	103	61680	40948	30531	24239	20011	16961	14647	12825	11347	10119	9078	
220	240	226	15,5	26	117	77344	51701	38571	30646	25324	21489	18583	16297	14445	12909	11609	
240	270	248	18	32	157	114883	76327	56970	452494	37457	31814	27543	24186	21469	19217	17315	
260	290	268	18	32,5	172	137892	91641	68430	54434	45047	38292	33183	29171	25927	23242	20975	
280	310	288	18,5	33	189	162818	108230	80842	64333	53264	45304	39287	34564	30749	27593	24931	
300	340	310	21	39	238	222238	147762	110405	87895	72810	61966	53774	47350	42163	37875	34263	
320	359	309	21	40	245	242704	161394	120617	96052	79594	67769	58838	51838	46188	41522	37592	
340	377	309	21	40	248	258967	172451	128604	102437	84909	72319	62814	55366	49358	44398	40222	
360	395	308	21	40	250	274693	182712	136596	108827	90231	76876	66798	58904	52663	47285	42865	
400	432	307	21	40	256	307960	204880	153212	124748	101288	86342	75070	66245	59134	53269	48340	
450	478	307	21	40	263	351465	233871	174943	139481	115752	98727	85893	75853	67768	61105	55509	
500	524	306	21	40	270	394970	262863	196675	156854	130216	111112	96717	85461	76402	68940	62678	
550	572	306	21	40	278	442313	294467	220322	175757	145955	124588	108493	95912	85793	77463	70475	
600	620	305	21	40	285	489657	325963	243974	194666	161700	138070	120277	106374	95195	85997	78284	

23

Travi