


Tubi RETTANGOLARI saldati da nastro

Qualità S 235JR (FE 360B)



dimensioni mm.	spessore mm.	peso Kg/m
70 x 30	1,5	2,30
	2	3,01
	3	4,45
	4	5,83
70 x 35	1,5	2,40
	2	3,20
	3	4,70
70 x 40	1,5	2,52
	2	3,33
	3	4,92
	4	6,46
70 x 50	1,5	2,74
	2	3,62
	3	5,36
	4	7,05
80 x 15	1,5	2,10
	2	2,80
80 x 20	1,5	2,30
	2	3,01
	3	4,45
80 x 30	1,5	2,52
	2	3,33
	3	4,92
	4	6,46
80 x 40	1,5	2,74
	2	3,62
	3	5,36
	4	7,05
80 x 50	1,5	3,00
	2	3,97
	3	5,88
	4	7,74
80 x 60	1,5	3,21
	2	4,26
	3	6,32
	4	8,33
90 x 30	1,5	2,74
	2	3,62
	3	5,36
	4	7,05
90 x 50	3	6,36
	4	8,50

dimensioni mm.	spessore mm.	peso Kg/m
100 x 20	1,5	2,74
	2	3,62
	3	5,36
100 x 30	1,5	3,00
	2	3,97
	3	5,88
100 x 40	1,5	3,22
	2	4,26
	3	6,32
	4	8,33
100 x 50	1,5	3,50
	2	4,60
	3	6,80
	4	8,90
100 x 60	2	4,90
	3	7,30
	4	9,50
100 x 80	3	8,40
	4	10,50
110 x 50	2	4,90
	3	7,30
120 x 30	2	4,60
	3	6,80
	4	9,50
120 x 40	2	4,90
	3	7,30
	4	9,50
	5	13,16
	6	15,80
	7	18,44
120 x 60	2	5,50
	3	8,20
	4	10,80
	5	13,16
120 x 80	2	6,15
	3	9,15
	4	12,05
	5	14,24
	6	16,43
130 x 50	2	5,50
	3	8,20
	4	10,80
130 x 60	2	7,48
	3	9,70